NOVALAB safety shower combination consisting of body shower with pull-rod actuation and eye/face shower for surface mounting, water connection on all sides



Attributes

- Pull rod guided, with triangle handle and sealing option
- Wall flange with toggle valve, wall bracket, safety shower head, eye and face shower with wall bracket
- Emergency shower head with nozzle holes and swirl discs for optimum spray jet
- Replaceable nozzle base, nickel-plated
- Self-draining shower head and wall bracket by gradient
- Fitting does not close automatically
- Emergency shower head 7 nozzle bores (approx. 60 l/min at 1.5 bar flow pressure)
- Vertical connecting pipe with wall flange for connecting the eye and face wash unit
- Eye shower unit with Wall bracket for precise positioning for stationary or flexible use
- Spiral pressure hose 1500 mm long for flexible use
- Eye wash unit with Flow regulator for constant water volume and spray height
- Eye wash unit with Dust protection cap to protect the jet former
- strainer to protect the eye wash unit
- Housing eye wash unit made of robust plastic, water-bearing parts on pressure side and water connection made of metal, green RAL 6032/ grey RAL 7035
- with hygiene flush module for cyclical flushing of water pipes at risk of stagnation Integrated programmable control electronics (selectable flushing times and intervals)
- Fulfils the requirements of DIN EN 15154-1 and -2 and the German BGI/GUV-I 850-0 ‘Safe working in laboratories’
- With safety signs ‘safety shower’ and ‘eye wash unit’ as stickers in accordance with ISO 3864-1
- With mounting material and technical product information

Variants	Art.-No.:
	60 1896 35

NovaLab GmbH
Brunsbütteler Damm 446
13591 Berlin

Phone +49 (0) 30 36 403 36 20
Fax +49 (0) 30 36 403 36 26
Mail: info@novalab-gmbh.de